

L3301/L3901/L4701

IMPLEMENTS



**ASSEMBLED
IN
GEORGIA**

Maximize Standard L-Series' versatility with Kubota's Performance-Matched quick attach/detach implements.

LA525 and LA765 Front Loaders

The LA525 and LA765 Front Loaders have a specially designed curved boom that can handle the big tasks that the Standard L-Series is made for, providing improved lifting power and height as well as exceptional durability.



Loaders Specifications

MODEL		LA525	LA765
2 Lever Quick Coupler		OPT	STD
Matching Tractor		L3301/L3901	L4701
Maximum Lift Height (Pivot pin)	In.(mm)	94.3 (2394)	105.2 (2673)
Clearance w/Attachment Dump	In.(mm)	76.2 (1936)	81.2 (2063)
Reach @ Maximum Height	In.(mm)	25.4 (645)	21.1 (537)
Maximum Dump Angle	deg.	40	41
Reach w/Attachment on Ground	In.(mm)	63.7 (1618)	70.2 (1783)
Maximum Rollback Angle	deg.	31	27
Digging Depth	In.(mm)	6.9 (176)	6.1 (156)
Overall Height in Carry Position	In.(mm)	51.3 (1302)	54.6 (1387)
Lift Capacity (Pivot pin)	lbs.(kg)	1131 (513)	1684 (764)
Lift Capacity (500 mm forward)	lbs.(kg)	855 (388)	1263 (573)

* Measures taken with Quick Coupler.

BH77 and BH92 Backhoes

The BH77 and BH92 Backhoes are "Performance-Matched" with the L3301, L3901 and L4701 to deliver more power and greater capacity. And, thanks to the full-flat deck, the backhoes deliver optimal legroom for maximum operator comfort.



Backhoes Specifications

MODEL		BH77	BH92
Matching Tractor		L3301/L3901	L4701
Transport height	In. (mm)	80.3 (2040)	100.1 (2544)
Stabilizer spread transport	In. (mm)	51.8 (1315)	69.2 (1758)
Ground clearance	In. (mm)	11.5 (292)	14.2 (360)
Digging depth, 2R. flat bottom	In. (mm)	89.8 (2280)	106.1 (2695)
Loading height	In. (mm)	65.7 (1669)	90.6 (2300)
Reach from swing pivot	In. (mm)	124.3 (3156)	149.6 (3801)
Swing pivot to rear axle center line	In. (mm)	37.6 (954)	40.9 (1040)
Bucket rotation	deg.	180	180
Stabilizer spread operating	In. (mm)	69.0 (1753)	93.3 (2369)

