



30964

RCF2760 & RCF2772 Models

Specifications & Capacities

Model Numbers	RCF2760	RCF2772
Machine Weight	955 lbs.	1,072 lbs.
Hitch	With front and rear Single Chain Guards	
Cutting Width	60"	72"
Overall Width	67"	79"
Overall Length	109"	121 3/4"
Deck Height (Bottom of Deck to Bottom of Skid Shoe)	11 1/4"	
Cutting Height	1 1/2" - 12"	
Cutting Capacity	3" Diameter	
Recommended Tractor PTO HP	35-130 HP	
PTO Speed	540 RPM	
Gearbox	540 RPM PTO driven gearbox, 1:1.44 speed-up beveled gears, cast iron housing, 1 3/8"-6 spline input shaft and 2" output shaft	
Gearbox Lubricant	EP 80-90W oil	
Gearbox oil Capacity	7 pints	
Deck Construction	All welded deck	
Deck Material Thickness	10 Gauge	
Side Skirt Material Thickness	1/4"	
Skid Construction	Replaceable bolt on skid shoes	
Stump Jumper	3/16" x 24" Round Pan	3/16" x 30 1/2" Round Pan
Blades (2)	1/2" x 4" x 25" Heat treated alloy steel free-swinging high lift	1/2" x 4" x 29" Heat treated alloy steel free-swinging high lift
Blade Bolts	Keyed with harden flat washers & lock nuts.	
Blade Tip Speed	12,384 FPM	14,861 FPM
Driveline	ASAE Category 4	
Driveline Protection	4 plate slip clutch	
Tailwheel Mount Assembly	Welded A-arm and caster fork with 360 degree swivel	
Tailwheel	4.00" x 8" x 15" Laminated tire with cast iron hub and tapered roller bearings	
Front Guard	Optional: Rubber Belting or Single Chain Guard	
Rear Guard	Single Chain Guard	